Installation guidelines Leafield litter bins Envirobank 140





Cleaning Products should be flushed with clean water and then washed with a mild detergent solution using a bristle brush or sponge. Care should be taken not to apply undue pressure that may damage labels. Flush clean with water after washing.




Tools Chalk, Hammer drill, 12mm masonry drill bit, Mallet, 17mm spanner Key:






Position the body in the required location and orientation, mark through the holes in the base to the ground below

Ground fixing kit additional components: Available as optional extra



Check - if fixing to pavement check that the hole positions are not too close to the edge of the paving slab (min 100mm from edge if possible)



Quality Standards All Leafield Environmental products are certificated to BS EN ISO



PPE Always wear appropriate PPE equipment and follow safety guidelines.



Remove the body to expose the ground below, clearly mark the positions of the four holes with a cross



Drilling holes and inserting bolts





Add washer. Push bolts through holes in bin locating into drilled ground holes



Use a mallet to drive the four bolts into the holes drilled in the ground through the moulded holes in the bin base


Drill 12mm holes at the four marked positions to a depth of 115mm to accommodate the ground fixing bolts



Drive the bolts in through the moulded holes until the tops sit flat on the bin base with the washer between bolt head and bin



Use a spanner or socket to tighten the bolts



Tighten the bolts to 22.0Nm torque for concrete. Tightening the bolts will fan out the bolt sheath in the hole holding the bolt secure



Once all bolts are tightened and secure close door





telephone

+ 44 (0)1225 816500

enter fax number

facsimile + 44 (0)1225 816501



website/email www.leafield-environmental.com recycle@leafieldenv.com



post Leafield Way, Leafield Industrial Estate Corsham, Wiltshire SN13 9UD