# Installation guide

## Octaplus Maxi



# **LEAFIELD** litter products





Cleaning Products should be rinsed with clean water and then washed with a mild detergent solution using a bristle brush or sponge. Care should be taken not to apply undue pressure that may damage labels. Flush clean with water after washing.



**Quality Standards** All Leafield Environmental products are certificated to BS EN ISO










Tools Chalk, Hammer, drill, 12mm masonry drill bit, 12.5mm drill bit, 17mm socket or spanner, Key.



PPE Always wear appropriate PPE equipment and follow safety guidelines.

## Marking out holes







the ground below using the bracket as a guide.



in body (as shown).

Leafield Way Leafield Industrial Estate Corsham, Wiltshire SN13 9UD



Telephone 01225 816500 01225 816501



litter@leafieldenv.com







Drill 3 x 12mm holes in the ground to a depth of 100mm to accommodate the bolt length and remove debris from holes.

Place bin base over drilled holes



Place anchor plate inside bin over the drilled holes

Insert fixings through the anchor plate and bin base and into the drilled holes. A hammer may be required.

Replace liner and hood. (LOCK)

#### Contents:

### From left to right:

3 x 12mm x 110mm fixings 1 x anchor plate





Post Leafield Way Leafield Industrial Estate Corsham, Wiltshire SN13 9UD



Telephone 01225 816500 Fax 01225 816501



**Email** litter@leafieldenv.com



